



PRODUCT DATA SHEET: CROSSGRIP TPO

Sep-18

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Length (m)	Widths (cm)	Weight (kg/m ²)
<i>Tolerances</i>	+/- 0.5	0+0.3	+/- 1	
Crossgrip TPO	12	10	75	5.2



GENERAL

APPEARANCES	Open grid “duckboard” design with cross directional top ribs.
COLOURS	Available in one homogenous standard colour; White.
DURABILITY	One piece welded construction for long life and minimal maintenance.
WORKABILITY	Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	Specifically engineered for roof walkways.

TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
COMPOSITION	Thermoplastic polyolefin
ENVIRONMENT	Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.** in any matting products. Crossgrip TPO is 100% recyclable. ** Registration, Evaluation, Authorisation and Restriction of CHemical substances
FIRE	EN ISO 13501-1:2007-Dfl-S1
SLIP RESISTANCE	ASTM F 1677 - Dry/Wet: 1.1/0.9 DIN 51130: R9, V10
WARRANTY	4 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf
WIND RESISTANCE	When loose laid, Crossgrip TPO is effective for winds up to 55mph (89 km/h). In Laboratory conditions, on a flat stable platform at The University Of Hertfordshire, School of Aerospace, Automotive & Design Engineering, Crossgrip TPO remained stable in wind speeds up to 88mph (142 km/h).



Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK
Tel: +44(0)1268 571116

Web: www.plastexmatting.com