

Animal cage matting

A top performer where comfort and cleanliness count.

HVD is a simple to cut and fit vinyl matting with a particularly smooth upper surface, which provides an extremely high level of cushioning and drainage, whilst also being hygienic, comfortable and easy to clean.

As a result of this special combination of benefits, HVD is ideal for lining kennel cages and is widely used in veterinary clinics and kennels.



BENEFITS

- Warm and comfortable
- High drainage
- Easy to clean
- Easy to cut on site, contours to uneven surfaces
- Quick to install


FEATURES

- Extra smooth surface
- Two layer construction
- Non-toxic and inert
- Made from flexible PVC
- Supplied in 10m rolls

STANDARD COLOURS



BLACK



BLUE

Other colours available on request.



STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*		
HVD	13.5mm (17/32")	10 x 0.6m (33' x 2')	10 x 0.91m (33' x 3')	10 x 1.22m (33' x 4')


*Contact us for bespoke dimensions.

PRODUCT DATA SHEET: HVD

Jun-18

SIZES & WEIGHTS

	All dimensions are nominal		Height (mm)	Length (m)	Widths (cm)		Weight (kg/m ²)
	Tolerances (mm)		+/- 0.5	0+0.3	+/- 1		
HVD	13.5	10	60	91	122	6.9	



GENERAL

APPEARANCES

Open grid with "D shaped" smooth top surface.

COLOURS

Available in homogenous standard colours; Black and Blue. Other colours available on request.

DURABILITY

One piece welded construction for maintenance free life.

WORKABILITY

Flexible construction is easy to cut and shape on site.
Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

USES

For animal cages in veterinary surgeries and kennels.

TECHNICAL DATA

ACOUSTIC

Excellent sound absorption properties.

CHEMICAL

Resistant to most acids, alkalines and oils. For specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf

COMPOSITION

Flexible DINP plasticised Polyvinyl Chloride (PVC).

ENVIRONMENT

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All products are 100% recyclable.
* Registration, Evaluation, Authorisation and Restriction of Chemical substances

HYGIENE

Non-porous 100% Virgin PVC - Inhibits the growth of bacteria.

REVERSION

Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

THERMAL

Functional -23°C +60°C (slight size variation may occur at temperature extremes).

UV LIGHT

Resistance to PVC degradation.

WARRANTY

2 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

PRODUCT DATA SHEET: HVD

ANCILLARIES



14mm x 60mm x 10.1m
(9/16" x 2 1/2" x 33')

60mm PVC edging strip

Supplied in rolls of 10.1m (33') length with cold welding paste.

Colours: Black, Dark Grey, Dark Brown, Holly Green, Oxford Blue, Yellow



14mm x 100mm x 10.1m
(9/16" x 3 3/4" x 33')

100mm PVC edging strip

Supplied in rolls of 10.1m (33') length with cold welding paste.

Colours: Black, Dark Grey, Yellow



15mm x 45mm x 2m
(5/8" x 1 13/16" x 6'6")

45mm Aluminium edging strip

Supplied in sections of 2m (6'6") length with fixing screws and plugs.

Colours: Anodised Aluminium, Powder Coated Yellow



14mm x 2.5m
(9/16" x 8'2")

Snap Track

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with welding paste.

Colours: Black, Dark Grey



Connector clips - Dual purpose

For joining sections of matting together side to side or end to end. Supplied in packs of 10.



Small floor hook

For securing sections of matting to floor. Supplied in packs of 10 with screws and plugs.



Large floor hook

For securing sections of matting to floor. Supplied in packs of 10 with screws and plugs.